

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Epoclear 2000, Epoxydharz-Einbettmittel

Revision date: 14.12.2018

Product code:

Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Epoclear 2000, Epoxydharz-Einbettmittel

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Epoxy resin hardener

Uses advised against

Any non-intended use.

1.3. Details of the supplier of the safety data sheet

Company name:	Schmitz-Metallographie GmbH	
Street:	Kaiserstraße 100	
Place:	D-52134 Herzogenrath	
Telephone:	02407 / 568296-0	Telefax: 02407 / 568296-9
e-mail:	info@schmitz-metallographie.de	
Contact person:	Herr Füllmann	
e-mail:	info@schmitz-metallographie.de	
Internet:	www.schmitz-metallographie.de	
Responsible Department:	Dr. Timo Gans-Eichler	e-mail: info@tge-consult.de
	Chemieberatung	Tel.: +49(0)251/394868-69
	Raesfeldstr. 22	www.tge-consult.de
	D-48149 Münster	

1.4. Emergency telephone number:

02407 / 568296-0 (Mo-Fr 9:00 - 16:00)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Acute toxicity: Acute Tox. 4

Acute toxicity: Acute Tox. 4

Acute toxicity: Acute Tox. 4

Skin corrosion/irritation: Skin Corr. 1B

Serious eye damage/eye irritation: Eye Dam. 1

Respiratory or skin sensitisation: Skin Sens. 1A

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Harmful if swallowed.

Harmful in contact with skin.

Harmful if inhaled.

Causes severe skin burns and eye damage.

Causes serious eye damage.

May cause an allergic skin reaction.

Harmful to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

benzyl alcohol

3-aminomethyl-3,5,5-trimethylcyclohexylamine

Octahydro-4,7-methano-1H-indene-dimethanamine

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Epoclear 2000, Epoxyharz-Einbettmittel

Revision date: 14.12.2018

Product code:

Page 2 of 14

Signal word: Danger

Pictograms:



Hazard statements

- H302+H312+H332 Harmful if swallowed, in contact with skin or if inhaled.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a POISON CENTER/doctor.
- P312 Call a POISON CENTER/doctor if you feel unwell.
- P405 Store locked up.
- P501 Dispose of contents/container to local/regional/national/international regulations.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Hardener for epoxy resins, stabilized

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
100-51-6	benzyl alcohol			25-50 %
	202-859-9	603-057-00-5	01-2119492630-38	
	Acute Tox. 4, Acute Tox. 4, Eye Irrit. 2; H332 H302 H319			
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine			25-50 %
	220-666-8	612-067-00-9	01-2119514687-32	
	Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1A, Aquatic Chronic 3; H312 H302 H314 H318 H317 H412			
68889-71-4	Octahydro-4.7-methano-1H-indene-dimethanamine			2,5-10 %
	272-573-7			
	Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Skin Sens. 1; H312 H302 H314 H317			
25513-64-8	2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine			<=2,5 %
	247-063-2		01-2119560598-25	
	Acute Tox. 4, Skin Corr. 1A, Eye Dam. 1, Skin Sens. 1A; H302 H314 H318 H317			

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Epoclear 2000, Epoxyharz-Einbettmittel

Revision date: 14.12.2018

Product code:

Page 3 of 14

Further Information

Product does not contain listed SVHC substances > 0,1 % according to Regulation (EC) No. 1907/2006 Article 59 (REACH)

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

In case of accident by inhalation: remove casualty to fresh air and keep at rest. In case of respiratory tract irritation, consult a physician. In the case of lung irritation: Primary treatment using corticoide spray, eg. Auxiloson spray, Pulmicort-dosage-spray. (Auxiloson and Pulmicort are registered trademarks).

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing. In case of skin irritation, consult a physician.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Observe risk of aspiration if vomiting occurs. Never give anything by mouth to an unconscious person or a person with cramps. When in doubt or if symptoms are observed, get medical advice.

4.2. Most important symptoms and effects, both acute and delayed

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Sand. Foam. Carbon dioxide (CO₂). Extinguishing powder. In case of major fire and large quantities: Water spray jet. Water mist.

Unsuitable extinguishing media

High power water jet

5.2. Special hazards arising from the substance or mixture

Can be released in case of fire: Carbon monoxide Carbon dioxide (CO₂). Nitrogen oxides (NO_x)

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. In case of fire: Wear self-contained breathing apparatus.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Co-ordinate fire-fighting measures to the fire surroundings.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment (refer to section 8).
Do not breathe vapour/aerosol. Avoid contact with skin, eyes and clothes.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Epoclear 2000, Epoxyharz-Einbettmittel

Revision date: 14.12.2018

Product code:

Page 4 of 14

barriers). Do not allow to enter into soil/subsoil.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Safe handling: see section 7

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Wear suitable protective clothing. (See section 8.)

Conditions to avoid: aerosol or mist formation

Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Usual measures for fire prevention.

Further information on handling

Advices on general occupational hygiene: See section 8.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Only use containers specifically approved for the substance/product.

Hints on joint storage

Do not store together with: Explosives. Oxidizing solids. Oxidizing liquids. Organic peroxides. Self-reactive substances and mixtures. Radioactive substances. Infectious substances.

Further information on storage conditions

Recommended storage temperature: 20°C

Protect against: Light. UV-radiation/sunlight. heat. moisture.

7.3. Specific end use(s)

See section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
100-51-6	benzyl alcohol			
	Consumer DNEL, long-term	oral	systemic	4 mg/kg bw/day
	Worker DNEL, acute	inhalation	systemic	110 mg/m ³
	Worker DNEL, long-term	inhalation	systemic	22 mg/m ³
	Consumer DNEL, acute	oral	systemic	20 mg/kg bw/day
	Consumer DNEL, acute	inhalation	systemic	27 mg/m ³
	Consumer DNEL, long-term	inhalation	systemic	5,4 mg/m ³
	Worker DNEL, long-term	dermal	systemic	8 mg/kg bw/day
	Consumer DNEL, acute	dermal	systemic	20 mg/kg bw/day

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Epoclear 2000, Epoxydharz-Einbettmittel

Revision date: 14.12.2018

Product code:

Page 5 of 14

Consumer DNEL, long-term	dermal	systemic	4 mg/kg bw/day
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine		
Worker , long-term	inhalation	local	0,073 mg/m ³
Consumer , long-term	oral	systemic	0,526 mg/kg bw/day
25513-64-8	2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine		
Consumer DNEL, long-term	oral	systemic	0.05 mg/kg bw/day

PNEC values

CAS No	Substance	Value
Environmental compartment		
100-51-6	benzyl alcohol	
Freshwater		1 mg/l
Freshwater (intermittent releases)		2,3 mg/l
Marine water		0,1 mg/l
Marine water (intermittent releases)		2,3 mg/l
Freshwater sediment		5,27 mg/kg
Marine sediment		0,527 mg/kg
Micro-organisms in sewage treatment plants (STP)		39 mg/l
Soil		0,456 mg/kg
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	
Freshwater		0,06 mg/l
Marine water		0,006 mg/l
Freshwater sediment		5,784 mg/kg
Micro-organisms in sewage treatment plants (STP)		3,18 mg/l
Soil		1,121 mg/kg
25513-64-8	2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	
Freshwater		0,102 mg/l
Freshwater (intermittent releases)		0,315 mg/l
Marine water		0,01 mg/l
Freshwater sediment		0,622 mg/kg
Marine sediment		0,062 mg/kg
Micro-organisms in sewage treatment plants (STP)		72 mg/l
Soil		10 mg/kg

Additional advice on limit values

To date, no national critical limit values exist.

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation.

Protective and hygiene measures

When using do not eat, drink or smoke.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Epoclear 2000, Epoxydharz-Einbettmittel

Revision date: 14.12.2018

Product code:

Page 6 of 14

Eye/face protection

Wear eye/face protection. DIN EN 166

Hand protection

Wear suitable gloves.

Suitable material:

FKM (fluororubber). - Thickness of glove material: 0,4 mm

Breakthrough time \geq 8 h

Butyl rubber. - Thickness of glove material: 0,5 mm

Breakthrough time \geq 8 h

CR (polychloroprenes, Chloroprene rubber). - Thickness of glove material: 0,5 mm

Breakthrough time \geq 8 h

NBR (Nitrile rubber). - Thickness of glove material: 0,35 mm

Breakthrough time \geq 8 h

PVC (Polyvinyl chloride). - Thickness of glove material: 0,5 mm

Breakthrough time \geq 8 h

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

Before using check leak tightness / impermeability. In the case of wanting to use the gloves again, clean them before taking off and air them well.

Skin protection

Suitable protective clothing: Lab apron.

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500.

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

-exceeding exposure limit values

-insufficient ventilation and aerosol or mist formation

Suitable respiratory protective equipment: particulates filter device (DIN EN 143). Type: P1-3

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

Environmental exposure controls

No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	yellowish
Odour:	amine-like
pH-Value:	No information available.

Changes in the physical state

Melting point:	No information available.
Initial boiling point and boiling range:	> 200 °C
Sublimation point:	No information available.
Softening point:	No information available.
Pour point:	No information available.
Flash point:	No information available.
Sustaining combustion:	No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Epoclear 2000, Epoxydharz-Einbettmittel

Revision date: 14.12.2018

Product code:

Page 7 of 14

Flammability

Solid: No information available.
Gas: No information available.

Explosive properties

none

Lower explosion limits: No information available.
Upper explosion limits: No information available.
Ignition temperature: > 100 °C

Auto-ignition temperature

Solid: No information available.
Gas: No information available.

Decomposition temperature: No information available.

Oxidizing properties

none

Vapour pressure:
(at 20 °C) No information available.
Vapour pressure:
(at 50 °C) No information available.
Density (at 20 °C): 1,018 g/cm³
Bulk density: No information available.
Water solubility: No information available.

Solubility in other solvents

No information available.

Partition coefficient: No information available.

Viscosity / dynamic:
(at 25 °C) 103 mPa·s

Viscosity / kinematic: No information available.

Flow time: No information available.

Vapour density: No information available.

Evaporation rate: No information available.

Solvent separation test: No information available.

Solvent content: No information available.

9.2. Other information

Solid content: No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No information available.

10.4. Conditions to avoid

Protect against: UV-radiation/sunlight. heat.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Epoclear 2000, Epoxydharz-Einbettmittel

Revision date: 14.12.2018

Product code:

Page 8 of 14

10.5. Incompatible materials

Materials to avoid: Oxidizing agents, strong. Reducing agents, strong.

10.6. Hazardous decomposition products

Can be released in case of fire: Carbon monoxide Carbon dioxide (CO₂). Nitrogen oxides (NO_x)

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicokinetics, metabolism and distribution

No information available.

Acute toxicity

Harmful if swallowed, in contact with skin or if inhaled.

ATEmix calculated

ATE (oral) 894,3 mg/kg; ATE (dermal) 1833,3 mg/kg; ATE (inhalation aerosol) 3,000 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
100-51-6	benzyl alcohol				
	oral	LD50 1230 mg/kg	Rat	ECHA Dossier	
	inhalation vapour	ATE 11 mg/l			
	inhalation aerosol	ATE 1,5 mg/l			
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine				
	oral	LD50 1030 mg/kg	Rat.	ECHA Dossier	
	dermal	ATE 1100 mg/kg			
	inhalation (4 h) aerosol	LC50 >5,01 mg/l	Rat.	ECHA Dossier	
68889-71-4	Octahydro-4.7-methano-1H-indene-dimethanamine				
	oral	LD50 503 mg/kg	Rat.		
	dermal	LD50 400 -500 mg/kg	Rat.		
25513-64-8	2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine				
	oral	LD50 910 mg/kg	Rat.	ECHA Dossier	

Irritation and corrosivity

Causes severe skin burns and eye damage.

Sensitising effects

May cause an allergic skin reaction. (3-aminomethyl-3,5,5-trimethylcyclohexylamine; Octahydro-4.7-methano-1H-indene-dimethanamine; 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

benzyl alcohol:

Chronic oral toxicity: Method: OECD 451. Species: Rat. Exposure duration: 2 years Result / evaluation:negative. Literature information: ECHA Dossier

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

In vitro mutagenicity/genotoxicity : Result / evaluation: negative.; Literature information: ECHA Dossier

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Epoclear 2000, Epoxydharz-Einbettmittel

Revision date: 14.12.2018

Product code:

Page 9 of 14

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

benzyl alcohol:

Chronic oral toxicity: Method: OECD 451. Species: Rat. Exposure duration: 2 years Result / evaluation: NOAEL = 400 mg/kg bw/day; Subacute inhalative toxicity :Method: OECD 412. Species: Rat. Exposure duration: 28d. Result / evaluation: NOAEC = 1072 mg/m³ Literature information: ECHA Dossier

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Subchronic oral toxicity: Method: OECD 408; Species: Rat.; Exposure duration: 90d; Result: NOAEL = 60 mg/kg bw/day.; Literature information: ECHA Dossier

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

The product has not been tested.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
100-51-6	benzyl alcohol					
	Acute fish toxicity	LC50 460 mg/l	96 h	Pimephales promelas	ECHA Dossier	
	Acute algae toxicity	ErC50 500 mg/l	72 h	Pseudokirchnella subcpitata	ECHA Dossier	
	Acute crustacea toxicity	EC50 230 mg/l	48 h	Daphnia magna	ECHA Dossier	
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine					
	Acute fish toxicity	LC50 110 mg/l	96 h	Leuciscus idus	ECHA Dossier	
	Acute algae toxicity	ErC50 >50 mg/l	72 h	Desmodesmus subspicatus	ECHA Dossier	
	Acute crustacea toxicity	EC50 23 mg/l	48 h	Daphnia Magna	ECHA Dossier	
	Crustacea toxicity	NOEC 3 mg/l	21 d	Daphnia magna	ECHA Dossier	
68889-71-4	Octahydro-4.7-methano-1H-indene-dimethanamine					
	Acute fish toxicity	LC50 110 mg/l	96 h	Salmo gairdneri		
25513-64-8	2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine					
	Acute fish toxicity	LC50 174 mg/l	96 h	Leuciscus idus (golden orfe)	ECHA Dossier	
	Acute algae toxicity	ErC50 mg/l 43,2	72 h	Pseudokirchneriella subcapitata	ECHA Dossier	
	Acute crustacea toxicity	EC50 mg/l 31,5	48 h	Daphnia magna	ECHA Dossier	
	Fish toxicity	NOEC mg/l >10,9	30 d	Brachydanio rerio (zebra-fish)	ECHA Dossier	OECD 210

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine			
	OECD 301A/ ISO 7827/ EEC 92/69V, C.4-A	8%	28	ECHA Dossier

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Epoclear 2000, Epoxydharz-Einbettmittel

Revision date: 14.12.2018

Product code:

Page 10 of 14

	Not readily biodegradable (according to OECD criteria)			
25513-64-8	2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine			
	EU Method C.4-A	7%	28	ECHA Dossier
	Not readily biodegradable (according to OECD criteria)			

12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
100-51-6	benzyl alcohol	1,05
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	0,99

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Dispose of waste according to applicable legislation. Consult the local waste disposal expert about waste disposal. Non-contaminated packages may be recycled. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.
Control report for waste code/ waste marking according to EAKV:

Waste disposal number of waste from residues/unused products

080199 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; wastes not otherwise specified

Waste disposal number of used product

080199 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; wastes not otherwise specified

Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:

UN 2735

14.2. UN proper shipping name:

AMINES, LIQUID, CORROSIVE, N.O.S.
(3-aminomethyl-3,5,5-trimethylcyclohexylamine,
Octahydro-4.7-methano-1H-indene-dimethanamine)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Epoclear 2000, Epoxyharz-Einbettmittel

Revision date: 14.12.2018

Product code:

Page 11 of 14

14.3. Transport hazard class(es):

8

14.4. Packing group:

II

Hazard label:

8



Classification code:

C7

Special Provisions:

274

Limited quantity:

1 L

Excepted quantity:

E2

Transport category:

2

Hazard No:

80

Tunnel restriction code:

E

Inland waterways transport (ADN)

14.1. UN number:

UN 2735

14.2. UN proper shipping name:

AMINES, LIQUID, CORROSIVE, N.O.S.
(3-aminomethyl-3,5,5-trimethylcyclohexylamine,
Octahydro-4.7-methano-1H-indene-dimethanamine)

14.3. Transport hazard class(es):

8

14.4. Packing group:

II

Hazard label:

8



Classification code:

C7

Special Provisions:

274

Limited quantity:

1 L

Excepted quantity:

E2

Marine transport (IMDG)

14.1. UN number:

UN 2735

14.2. UN proper shipping name:

AMINES, LIQUID, CORROSIVE, N.O.S.
(3-aminomethyl-3,5,5-trimethylcyclohexylamine,
Octahydro-4.7-methano-1H-indene-dimethanamine)

14.3. Transport hazard class(es):

8

14.4. Packing group:

II

Hazard label:

8



Marine pollutant:

NO

Special Provisions:

274

Limited quantity:

1 L

Excepted quantity:

E2

EmS:

F-A, S-B

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:

UN 2735

14.2. UN proper shipping name:

AMINES, LIQUID, CORROSIVE, N.O.S.
(3-aminomethyl-3,5,5-trimethylcyclohexylamine,
Octahydro-4.7-methano-1H-indene-dimethanamine)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Epoclear 2000, Epoxydharz-Einbettmittel

Revision date: 14.12.2018

Product code:

Page 12 of 14

14.3. Transport hazard class(es): 8

14.4. Packing group: II

Hazard label: 8



Special Provisions: A3 A803

Limited quantity Passenger: 0.5 L

Passenger LQ: Y840

Excepted quantity: E2

IATA-packing instructions - Passenger: 851

IATA-max. quantity - Passenger: 1 L

IATA-packing instructions - Cargo: 855

IATA-max. quantity - Cargo: 30 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Safe handling: see section 7

Personal protection equipment: see section 8

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not relevant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2010/75/EU (VOC): No information available.

2004/42/EC (VOC): No information available.

Information according to 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

Additional information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

REACH 1907/2006 Appendix XVII, No (mixture): 3

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Water contaminating class (D): 2 - clearly water contaminating

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

benzyl alcohol

3-aminomethyl-3,5,5-trimethylcyclohexylamine

SECTION 16: Other information

Changes

Rev 1,00 Initial release: 14.12.2018

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen

CAS Chemical Abstracts Service

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Epoclear 2000, Epoxydharz-Einbettmittel

Revision date: 14.12.2018

Product code:

Page 13 of 14

DNEL: Derived No Effect Level
 IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
 ICAO: International Civil Aviation Organization
 ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals
 GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)
 LOAEL: Lowest observed adverse effect level
 LOAEC: Lowest observed adverse effect concentration
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 NOAEL: No observed adverse effect level
 NOAEC: No observed adverse effect level
 NTP: National Toxicology Program
 N/A: not applicable
 OSHA: Occupational Safety and Health Administration
 PNEC: predicted no effect concentration
 PBT: Persistent bioaccumulative toxic
 RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 SARA: Superfund Amendments and Reauthorization Act
 SVHC: substance of very high concern
 TRGS Technische Regeln fuerGefahrstoffe
 TSCA: Toxic Substances Control Act
 VOC: Volatile Organic Compounds
 VwVwS: Verwaltungsvorschrift wassergefaehrdender Stoffe
 WGK: Wassergefaehrungsklasse

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Acute Tox. 4; H302	Calculation method
Acute Tox. 4; H312	Calculation method
Acute Tox. 4; H332	Calculation method
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1A; H317	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H302 Harmful if swallowed.
 H302+H312+H332 Harmful if swallowed, in contact with skin or if inhaled.
 H312 Harmful in contact with skin.
 H314 Causes severe skin burns and eye damage.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.
 H412 Harmful to aquatic life with long lasting effects.

Further Information

Classification according EC regulation 1272/2008 (CLP): - Classification procedure:
 Health hazards: Calculation method.
 Environmental hazards: Calculation method.
 Physical hazards: On basis of test data and / or calculated and / or estimated.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Epoclear 2000, Epoxyharz-Einbettmittel

Revision date: 14.12.2018

Product code:

Page 14 of 14

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)